

Instruction

1.Removing a spool from a case～
Removing a tape

TANAKA DENSHI KOGYO K.K

Quality Assurance Dpt.



①Open the upper case while pressing the edge of the bottom case with fingers as shown in the figure.



①Open the upper case while pressing the edge of the bottom case with fingers as shown in the figure.




①Open the upper case while pressing the edge of the bottom case with fingers as shown in the figure.




①Open the upper case while pressing the edge of the bottom case with fingers as shown in the figure.



①Open the upper case while pressing the edge of the bottom case with fingers as shown in the figure.



①Open the upper case while pressing the edge of the bottom case with fingers as shown in the figure.



①Open the upper case while pressing the edge of the bottom case with fingers as shown in the figure.




①Open the upper case while pressing the edge of the bottom case with fingers as shown in the figure.



①Open the upper case while pressing the edge of the bottom case with fingers as shown in the figure.




①Open the upper case while pressing the edge of the bottom case with fingers as shown in the figure.



①Open the upper case while pressing the edge of the bottom case with fingers as shown in the figure.



②Hold the center of the spool while pressing the bottom case and pull the spool vertically.




②Hold the center of the spool while pressing the bottom case and pull the spool vertically.




②Hold the center of the spool while pressing the bottom case and pull the spool vertically.



②Hold the center of the spool while pressing the bottom case and pull the spool vertically.



②Hold the center of the spool while pressing the bottom case and pull the spool vertically.




③Turn the spool sideways while holding the center of the spool.




③Turn the spool sideways while holding the center of the spool.



③Turn the spool sideways while holding the center of the spool.




③Turn the spool sideways while holding the center of the spool.



③Turn the spool sideways while holding the center of the spool.




③Turn the spool sideways while holding the center of the spool.




④Peel off half the edge of the tape with tweezers, then pinch the wire and the tape together.


④Peel off half the edge of the tape with tweezers, then pinch the wire and the tape together.




④Peel off half the edge of the tape with tweezers, then pinch the wire and the tape together.




④Peel off half the edge of the tape with tweezers, then pinch the wire and the tape together.




④Peel off half the edge of the tape with tweezers, then pinch the wire and the tape together.




④Peel off half the edge of the tape with tweezers, then pinch the wire and the tape together.




④Peel off half the edge of the tape with tweezers, then pinch the wire and the tape together.




④Peel off half the edge of the tape with tweezers, then pinch the wire and the tape together.



④Peel off half the edge of the tape with tweezers, then pinch the wire and the tape together.




④Peel off half the edge of the tape with tweezers, then pinch the wire and the tape together.




④Peel off half the edge of the tape with tweezers, then pinch the wire and the tape together.




④Peel off half the edge of the tape with tweezers, then pinch the wire and the tape together.




④Peel off half the edge of the tape with tweezers, then pinch the wire and the tape together.




④Peel off half the edge of the tape with tweezers, then pinch the wire and the tape together.




④Peel off half the edge of the tape with tweezers, then pinch the wire and the tape together.




④Peel off half the edge of the tape with tweezers, then pinch the wire and the tape together.




④Peel off half the edge of the tape with tweezers, then pinch the wire and the tape together.




⑤Peel the wire and the tape
together then retain the folded wire
in the notch.




⑤Peel the wire and the tape
together then retain the folded wire
in the notch.



⑤Peel the wire and the tape
together then retain the folded wire
in the notch.




⑤Peel the wire and the tape
together then retain the folded wire
in the notch.



⑤Peel the wire and the tape
together then retain the folded wire
in the notch.



⑤Peel the wire and the tape
together then retain the folded wire
in the notch.



⑤Peel the wire and the tape
together then retain the folded wire
in the notch.




⑤Peel the wire and the tape
together then retain the folded wire
in the notch.



⑤Peel the wire and the tape
together then retain the folded wire
in the notch.



⑤Peel the wire and the tape
together then retain the folded wire
in the notch.



⑤Peel the wire and the tape
together then retain the folded wire
in the notch.




⑥Peel off only the tape and keep the wire at the edge of the notch.




⑥Peel off only the tape and keep the wire at the edge of the notch.



⑥Peel off only the tape and keep the wire at the edge of the notch.




⑥Peel off only the tape and keep the wire at the edge of the notch.




⑥Peel off only the tape and keep the wire at the edge of the notch.




⑥Peel off only the tape and keep the wire at the edge of the notch.




⑥Peel off only the tape and keep the wire at the edge of the notch.




⑥Peel off only the tape and keep the wire at the edge of the notch.




⑥Peel off only the tape and keep the wire at the edge of the notch.



⑥Peel off only the tape and keep the wire at the edge of the notch.




⑥Peel off only the tape and keep the wire at the edge of the notch.



⑥Peel off only the tape and keep the wire at the edge of the notch.



⑥Peel off only the tape and keep the wire at the edge of the notch.



⑥Peel off only the tape and keep the wire at the edge of the notch.




⑥Peel off only the tape and keep the wire at the edge of the notch.




⑦Change hands and hold the center of the spool with one hand.



⑦Change hands and hold the center of the spool with one hand.




⑦Change hands and hold the center of the spool with one hand.




⑦Change hands and hold the center of the spool with one hand.



⑦Change hands and hold the center of the spool with one hand.



⑦Change hands and hold the center of the spool with one hand.



⑦Change hands and hold the center of the spool with one hand.



⑧Hold the wire and rotate the spool slowly to unwind it.




⑧Hold the wire and rotate the spool slowly to unwind it.



⑧Hold the wire and rotate the spool slowly to unwind it.



⑧Hold the wire and rotate the spool slowly to unwind it.




⑧Hold the wire and rotate the spool slowly to unwind it.




⑧Hold the wire and rotate the spool slowly to unwind it.




⑧Hold the wire and rotate the spool slowly to unwind it.




⑧Hold the wire and rotate the spool slowly to unwind it.



⑧Hold the wire and rotate the spool slowly to unwind it.




⑧Hold the wire and rotate the spool slowly to unwind it.



⑧Hold the wire and rotate the spool slowly to unwind it.




⑧Hold the wire and rotate the spool slowly to unwind it.




⑧Hold the wire and rotate the spool slowly to unwind it.




⑨Keep holding the wire and pass it slowly through the notch on the opposite side of the flange.




⑨Keep holding the wire and pass it slowly through the notch on the opposite side of the flange.




⑨Keep holding the wire and pass it slowly through the notch on the opposite side of the flange.




⑨Keep holding the wire and pass it slowly through the notch on the opposite side of the flange.




⑨Keep holding the wire and pass it slowly through the notch on the opposite side of the flange.




⑨Keep holding the wire and pass it slowly through the notch on the opposite side of the flange.




⑨Keep holding the wire and pass it slowly through the notch on the opposite side of the flange.




⑨Keep holding the wire and pass it slowly through the notch on the opposite side of the flange.



⑨Keep holding the wire and pass it slowly through the notch on the opposite side of the flange.



⑨Keep holding the wire and pass it slowly through the notch on the opposite side of the flange.



⑨Keep holding the wire and pass it slowly through the notch on the opposite side of the flange.